

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP BRAKE FLUSH 5GL

Material number : 00000000000053535

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Emergency** : In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Vehicle Maintenance

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	liquid
Colour	colourless
Odour	hydrocarbon-like

**GHS Classification**

Flammable liquids : Category 2  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Specific target organ toxicity - single exposure : Category 1  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
 Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H370 Causes damage to organs.

Precautionary statements : **Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.  
 P331 Do NOT induce vomiting.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P235 Keep cool.

**Disposal:**  
 P501 Dispose of contents/container in accordance with local regulation.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
---------------	---------	-------------------

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

acetone	67-64-1	>= 50 - < 70
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
propan-2-ol	67-63-0	>= 3 - < 5
heptane	142-82-5	>= 1 - < 3
methanol	67-56-1	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

- General advice : Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off with soap and water. Take off contaminated clothing and shoes immediately. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
- In case of eye contact : If in eyes, rinse with water for 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling, respiratory issues, and general pain. Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration, contact time). May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Causes damage to organs. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

---

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Dry chemical  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Refer to protective measures listed in sections 7 and 8.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent further leakage or spillage.  
Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.
- 

**SECTION 7. HANDLING AND STORAGE**

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours or spray mist.  
Keep away from fire, sparks and heated surfaces.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents  
Do not freeze.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
		STEL	750 ppm 1,780 mg/m <sup>3</sup>	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m <sup>3</sup>	CAL PEL
		propan-2-ol	67-63-0	TWA
STEL	400 ppm			ACGIH
TWA	400 ppm 980 mg/m <sup>3</sup>			NIOSH REL
ST	500 ppm 1,225 mg/m <sup>3</sup>			NIOSH REL
TWA	400 ppm 980 mg/m <sup>3</sup>			OSHA Z-1
TWA	400 ppm 980 mg/m <sup>3</sup>			OSHA P0
STEL	500 ppm			OSHA P0

## ZEP BRAKE FLUSH 5GL

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

			1,225 mg/m3	
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
		C	1,000 ppm	CAL PEL
		PEL	200 ppm 260 mg/m3	CAL PEL
		STEL	250 ppm 325 mg/m3	CAL PEL

## Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of	15 mg/l	ACGIH BEI

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

				shift (As soon as possible after exposure ceases)		
--	--	--	--	---	--	--

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves  
: Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Ensure that eyewash stations and safety showers are close to the workstation location.  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : 55.5 °C

Flash point : < -18 °C  
Method: closed cup

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
	No data available
Vapour pressure	: not determined
Relative vapour density	: No data available
Density	: 0.72 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
	No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SECTION 11. TOXICOLOGICAL INFORMATION****Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

function or change, which may include cramping, swelling, respiratory issues, and general pain.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Effects are dependent on exposure (dose, concentration, contact time).

**Carcinogenicity:**
**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Acute toxicity**
**Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:**
**acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l  
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

**propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
Method: Calculation method

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

**heptane:**  
Acute inhalation toxicity : LC50 Rat: 103 mg/l  
Exposure time: 4 h

**Skin corrosion/irritation**

**Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information**

**Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Remarks: No data available

**Components:****heptane :**

Partition coefficient: n-octanol/water : log Pow: 5

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., May cause long lasting harmful effects to aquatic life.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues

: Dispose of in accordance with local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging

: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): UN1993, Flammable liquids, n.o.s., (ACETONE, HEPTANE), 3, II
--

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

Transportation Regulation: IMDG (Vessel):  
UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, HEPTANE), 3, II

Transportation Regulation: IATA (Cargo Air):  
UN1993, Flammable liquid, n.o.s., (ACETONE, HEPTANE), 3, II

Transportation Regulation: IATA (Passenger Air):  
UN1993, Flammable liquid, n.o.s., (ACETONE, HEPTANE), 3, II

Transportation Regulation: TDG (Canada):  
UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, HEPTANE), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
methanol 67-56-1 1.4645 %

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

**California Prop. 65**



**WARNING:** This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**

Hazard pictograms :



Signal word :

**Danger:**

Hazard statements :

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs.

Precautionary statements :

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and

**ZEP BRAKE FLUSH 5GL**

Version 4.0

Revision Date 05/03/2018

Print Date 01/07/2019

receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Keep cool.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	4.0
Revision Date:	05/03/2018
Print Date:	01/07/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.