

DOD Hazardous Materials Information System
DoD 6050.5-L
AS OF July 1998

FSC: 9150
NIIN: 00F025509
Manufacturer's CAGE: 0E7F8
Part No. Indicator: A
Part Number/Trade Name: BC601 PNEUMATIC TOOL LUBRICANTS

=====

General Information

=====

Item Name: LUBRICANT
Company's Name: STANLEY-BOSTITCH
Company's Street: ROUTE 2
Company's P. O. Box: N/K
Company's City: EAST GREENWICH
Company's State: RI
Company's Country: US
Company's Zip Code: 02818
Company's Emerg Ph #: 401-884-2500
Company's Info Ph #: 401-884-2500
Distributor/Vendor # 1:
Distributor/Vendor # 1 Cage:
Distributor/Vendor # 2:
Distributor/Vendor # 2 Cage:
Distributor/Vendor # 3:
Distributor/Vendor # 3 Cage:
Distributor/Vendor # 4:
Distributor/Vendor # 4 Cage:
Safety Data Action Code:
Safety Focal Point: F
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SE
Date MSDS Prepared: 01JAN91
Safety Data Review Date: 16NOV92
Supply Item Manager:
MSDS Preparer's Name:
Preparer's Company: STANLEY-BOSTITCH
Preparer's St Or P. O. Box: ROUTE 2
Preparer's City: EAST GREENWICH
Preparer's State: RI
Preparer's Zip Code: 02818
Other MSDS Number:
MSDS Serial Number: BPSCV
Specification Number:
Spec Type, Grade, Class:
Hazard Characteristic Code:
Unit Of Issue:
Unit Of Issue Container Qty:
Type Of Container:
Net Unit Weight:

Report for NIIN: 00F025509

NRC/State License Number:
Net Explosive Weight:
Net Propellant Weight-Ammo:
Coast Guard Ammunition Code:

=====

Ingredients/Identity Information

```

=====
Proprietary: NO
Ingredient: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY
PARAFFINIC, LUBRICATING OIL BASE STOCK
Ingredient Sequence Number: 01
Percent: N/K
Ingredient Action Code:
Ingredient Focal Point: F
NIOSH (RTECS) Number: PY8040500
CAS Number: 64741-88-4
OSHA PEL: 5 MG/CUM
ACGIH TLV: 5 MG/CUM
Other Recommended Limit: N/K
=====

```

Physical/Chemical Characteristics

```

=====
Appearance And Odor: PALE CLEAR LIQUID, PETROLEUM ODOR.
Boiling Point: N/K
Melting Point: N/K
Vapor Pressure (MM Hg/70 F): <0.01
Vapor Density (Air=1): >12
Specific Gravity: 0.875
Decomposition Temperature: N/K
Evaporation Rate And Ref: (BU AC = 1): <0.01
Solubility In Water: NEGLIGIBLE
Percent Volatiles By Volume: NEGL
Viscosity:
pH: N/K
Radioactivity:
Form (Radioactive Matl):
Magnetism (Milligauss):
Corrosion Rate (IPY): N/K
Autoignition Temperature:
=====

```

Fire and Explosion Hazard Data

```

=====
Flash Point: 141C/285F
Flash Point Method: COC
Lower Explosive Limit: 1%
Upper Explosive Limit: 6%
Extinguishing Media: DRY CHEMICAL, FOAM, CO2
Special Fire Fighting Proc: USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire And Expl Hazrds: N/K
=====

```

Report for NIIN: 00F025509

Reactivity Data

```

=====
Stability: YES
Cond To Avoid (Stability): N/K
Materials To Avoid: STRONG OXIDIZERS
Hazardous Decomp Products: CO
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): N/K
=====

```

Health Hazard Data

```

=====
LD50-LC50 Mixture: N/K
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
=====

```

Route Of Entry - Ingestion: NO
 Health Haz Acute And Chronic: EYES/SKIN: IRRITATION. INHALATION: LUNG IRRITATION.
 Carcinogenicity - NTP: NO
 Carcinogenicity - IARC: NO
 Carcinogenicity - OSHA: NO
 Explanation Carcinogenicity: NONE
 Signs/Symptoms Of Overexp: N/K
 Med Cond Aggravated By Exp: N/K
 Emergency/First Aid Proc: SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/ PLENTY OF WATER FOR 15 MIN. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====

Precautions for Safe Handling and Use

=====

Steps If Matl Released/Spill: PREVENT SPREAD OF SPILL, ABSORB W/SAND OR INERT MATERIALS, SWEEP OR SCOOP UP & REMOVE.
 Neutralizing Agent: N/K
 Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.
 Precautions-Handling/Storing: USE METHODS GENERALLY ADVOCATED FOR PETROLEUM PRODUCTS. DON'T MIX W/OXIDIZING MATERIALS.
 Other Precautions: AVOID PROLONGED OR REPEATED CONTACT W/SKIN, INHALATION OF FUMES.

=====

Control Measures

=====

Respiratory Protection: AS REQUIRED
 Ventilation: LOCAL EXHAUST
 Protective Gloves: RECOMMENDED
 Eye Protection: GOGGLES
 Other Protective Equipment: APRON
 Work Hygienic Practices: DON'T WEAR CONTAMINATED CLOTHING.
 Suppl. Safety & Health Data: N/K

Report for NIIN: 00F025509

=====

Transportation Data

=====

Transportation Action Code:
 Transportation Focal Point:
 Trans Data Review Date:
 DOT PSN Code:
 DOT Symbol:
 DOT Proper Shipping Name:
 DOT Class:
 DOT ID Number:
 DOT Pack Group:
 DOT Label:
 DOT/DoD Exemption Number:
 IMO PSN Code:
 IMO Proper Shipping Name:
 IMO Regulations Page Number:
 IMO UN Number:
 IMO UN Class:
 IMO Subsidiary Risk Label:
 IATA PSN Code:
 IATA UN ID Number:
 IATA Proper Shipping Name:
 IATA UN Class:

IATA Subsidiary Risk Class:
 IATA Label:
 AFI PSN Code:
 AFI Symbols:
 AFI Prop. Shipping Name:
 AFI Class:
 AFI ID Number:
 AFI Pack Group:
 AFI Label:
 AFI Special Prov:
 AFI Basic Pac Ref:
 MMAC Code:
 N.O.S. Shipping Name:
 Additional Trans Data:

=====

Disposal Data

=====

Disposal Data Action Code:
 Disposal Data Focal Point:
 Disposal Data Review Date:
 Rec # For This Disp Entry:
 Tot Disp Entries Per NSN:
 Landfill Ban Item:
 Disposal Supplemental Data:
 1st EPA Haz Wst Code New:
 1st EPA Haz Wst Name New:
 1st EPA Haz Wst Char New:
 1st EPA Acute Hazard New:
 2nd EPA Haz Wst Code New:

Report for NIIN: 00F025509

2nd EPA Haz Wst Name New:
 2nd EPA Haz Wst Char New:
 2nd EPA Acute Hazard New:
 3rd EPA Haz Wst Code New:
 3rd EPA Haz Wst Name New:
 3rd EPA Haz Wst Char New:
 3rd EPA Acute Hazard New:

=====

Label Data

=====

Label Required: YES
 Technical Review Date: 16NOV92
 Label Date: 27OCT92
 MFR Label Number: N/R
 Label Status: F
 Common Name: PETROLEUM OIL
 Chronic Hazard: NO
 Signal Word: CAUTION!
 Acute Health Hazard-None:
 Acute Health Hazard-Slight: X
 Acute Health Hazard-Moderate:
 Acute Health Hazard-Severe:
 Contact Hazard-None:
 Contact Hazard-Slight: X
 Contact Hazard-Moderate:
 Contact Hazard-Severe:
 Fire Hazard-None:
 Fire Hazard-Slight: X
 Fire Hazard-Moderate:

Fire Hazard-Severe:
Reactivity Hazard-None: X
Reactivity Hazard-Slight:
Reactivity Hazard-Moderate:
Reactivity Hazard-Severe:
Special Hazard Precautions: EYES/SKIN: IRRITATION. INHALATION: LUNG
IRRITATION. RRHEA/NERVOUS SYSTEM IMPAIRMENT. CARCINOGEN: FORMALDEHYDE.
Protect Eye: Y
Protect Skin: Y
Protect Respiratory: Y
Label Name: STANLEY-BOSTITCH
Label Street: ROUTE 2
Label P.O. Box: N/K
Label City: EAST GREENWICH
Label State: RI
Label Zip Code: 02818
Label Country: US
Label Emergency Number: 401-884-2500
Year Procured: UNK