

Safety Data Sheet E-Z TRAC AEROSOL, M/M

Supersedes Date 06/27/2013

Issuing Date 09/23/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name E-Z TRAC AEROSOL, M/M
Recommended use Solvent-borne coatings
Information on Manufacturer
CHEMSEARCH DIV. OF NCH CORP.
BOX 152170
IRVING, TX 75015

Product Code 5673
Chemical nature Epoxy
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Colorless

Physical state Liquid

Odor Epoxy

GHS

Classification

Physical Hazards

Flammable Aerosols
Gases under pressure

Category 1
Liquefied gas

Health Hazard

Acute Oral Toxicity
Acute Dermal Toxicity
Acute Inhalation Toxicity - Gas
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Skin sensitization
Reproductive Toxicity
Carcinogenicity
Specific target organ systemic toxicity (single exposure)
Specific target organ toxicity (repeated exposure)

Category 4
Category 4
Category 4
Category 2
Category 2A
Category 1
Category 2
Category 2
Category 2
Category 3
Category 2

Other hazards

None

Labeling

Signal Word

DANGER



Hazard statements

H222 - Extremely flammable aerosol
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H317 - May cause an allergic skin reaction
H315 - Causes skin irritation
H312 - Harmful in contact with skin
H319 - Causes serious eye irritation
H302 - Harmful if swallowed
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames or hot surfaces.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe vapor or mist
P271 - Use in a well-ventilated area.
P280 - Wear protective gloves, protective clothing and eye protection.
P264 - Wash face, hands and any exposed skin thoroughly after handling
P272 - Contaminated work clothing should not be allowed out of the workplace
P270 - Do not eat, drink or smoke when using this product.
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a physician if unwell.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P333 + P313 - If skin irritation or rash occurs, get medical attention
P362 - Take off contaminated clothing and wash before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists, get medical attention.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a

physician if unwell.

P403 - Store in a well-ventilated place

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents and container in accordance with applicable local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %
Acetone	67-64-1	15-40
Propane	74-98-6	10-30
Xylenes (o-, m-, p- isomers)	1330-20-7	10-30
Toluene	108-88-3	10-30
Butane	106-97-8	10-30
Ethyl benzene	100-41-4	5-10
Methyl ethyl ketoxime	96-29-7	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, or gas.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Inhalation	Move to fresh air. In case of shortness of breath, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person. Rinse mouth.
Notes to physician	May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Flash Point -134 °F / -92 °C

Method No data available

Flammability Limits in Air %: Mixture.

Upper: 12.5

Lower: 0.8

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

Do not use straight stream of water for fire fighting as the burning material may be spread.

Specific hazards arising from the chemical

Extremely flammable. Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: 30 inches / >76 cm and Burnback: 5 inch / >12 cm.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) -

3

NFPA Health 2

Flammability 4

Instability 0

HMIS Health 2

Flammability 4

Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Take precautionary measures against static discharges. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.			
Storage	Keep away from heat and sources of ignition. Keep in a dry, cool and well-ventilated place. Store in original container.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	122 °F / 50 °C
Storage Conditions	Indoor	X	Outdoor	
			Heated	Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Acetone	TWA: 500 ppm STEL: 750 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³	2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³	No data available
Toluene	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	500 ppm STEL 150 ppm STEL 560 mg/m ³ TWA: 100 ppm TWA: 375 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Ethyl benzene	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	800 ppm STEL 125 ppm STEL 545 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin Protection

Wear suitable protective clothing, Impervious gloves.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Viscosity	Non viscous
Color	Colorless	Odor	Epoxy
Odor Threshold	Not applicable	Appearance	Transparent
pH	Not applicable	Specific Gravity	0.76
Evaporation Rate	>1 (Butyl acetate=1)	Percent Volatile (Volume)	0
VOC Content (%)	54.8	VOC Photoreactive (Y/N)	Yes
VOC Content (g/L)	413	Vapor Pressure	2317 hPa
Vapor Density	No information available	Solubility	Negligible
n-Octanol/Water Partition	No data available	Melting Point/Range	No data available
Decomposition Temperature	No data available	Boiling Point/Range	92 °F / 33 °C
Flammability (solid, gas)	No data available		
Flash Point	-134 °F / -92 °C	Method	No data available
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Mixture	Upper: 12.5 Lower: 0.8	

10. STABILITY AND REACTIVITY

Chemical Stability

Stable. Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from open flames, hot surfaces, and sources of ignition.

Incompatible Products

Strong oxidizing agents, Acids, Nitrates, Halogens, Fluorine, Chlorine.

Decomposition Temperature

No data available

Hazardous Decomposition Products

No information available.

Possibility of Hazardous Reactions

None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 No information available

Dermal LD50 No information available

Inhalation LC50

Gas 11,090.03

Mist No information available

Vapor No information available

Principle Route of Exposure Inhalation, Skin contact, Eye contact.

Primary Routes of Entry Skin contact, Skin Absorption.

Acute Effects:

Eyes Causes serious eye irritation.

Skin Causes skin irritation. May be absorbed through the skin in harmful amounts. May cause allergic skin reaction.

Inhalation May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. May cause cardiac arrhythmia.

Ingestion Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity Repeated and prolonged exposure to solvents may cause brain and nervous system damage. May cause irregular heartbeats, especially under conditions of stress. May cause cardiac arrhythmia. Contains a known or suspected reproductive toxin. Contains a known or suspected carcinogen. Liver and kidney injuries may occur. May cause sensitization by skin contact.

Target Organ Effects Central nervous system, Respiratory system, Reproductive System, Kidney, Liver, Eyes, Skin.

Aggravated Medical Conditions Neurological disorders, Respiratory disorders, Kidney disorders, Liver disorders, Skin disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Acetone 67-64-1	No data available	no data available	= 50100 mg/m ³ (Rat) 8 h	No data available	No data available
Propane 74-98-6	No data available	no data available	= 658 mg/L (Rat) 4 h	No data available	No data available
Xylenes (o-, m-, p- isomers) 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h	No data available	No data available
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit) = 12124 mg/kg (Rat)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h	No data available	No data available
Butane 106-97-8	No data available	no data available	= 658 g/m ³ (Rat) 4 h	No data available	No data available
Ethyl benzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h	No data available	No data available
Methyl ethyl ketoxime 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h	No data available	No data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Acetone 67-64-1	No data available	No data available	No data available	No data available	Skin; Central nervous system; Eyes; Respiratory system
Propane 74-98-6	No data available	No data available	No data available	No data available	Central nervous system
Toluene 108-88-3	No data available	No data available	yes	yes	Skin; Central nervous system; Eyes; Respiratory system; Liver; Kidney; Reproductive System
Butane 106-97-8	No data available	No data available	No data available	No data available	Central nervous system
Ethyl benzene 100-41-4	No data available	No data available	No data available	No data available	Skin; Central nervous system; Eyes; Respiratory system
Methyl ethyl ketoxime 96-29-7	No data available	skin sensitizer	No data available	No data available	No data available

Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Other
Xylenes (o-, m-, p- isomers) 1330-20-7	not applicable	Group 3	not applicable	not applicable	not applicable
Toluene 108-88-3	not applicable	Group 3	not applicable	not applicable	not applicable
Ethyl benzene 100-41-4	A3	Group 2B	not applicable	X	not applicable

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	Partition coefficient
Acetone	No information available.	LC50 4.74 - 6.33 mL/L Oncorhynchus mykiss 96 h LC50 6210 - 8120 mg/L Pimephales promelas 96 h LC50 = 8300 mg/L Lepomis macrochirus 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50	-0.24
Propane	No information available.	No information available.	No information available	No information available.	2.3
Xylenes (o-, m-, p- isomers)	EC50 = 11 mg/L Pseudokirchneriella subcapitata 72 h	LC50 = 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50 = 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50 = 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50	3.15
Toluene	EC50 > 433 mg/L Pseudokirchneriella subcapitata 96 h EC50 = 12.5 mg/L Pseudokirchneriella subcapitata 72 h	LC50 15.22 - 19.05 mg/L Pimephales promelas 96 h LC50 = 12.6 mg/L Pimephales promelas 96 h LC50 5.89 - 7.81 mg/L Oncorhynchus mykiss 96 h LC50 14.1 - 17.16 mg/L Oncorhynchus mykiss 96 h LC50 = 5.8 mg/L Oncorhynchus mykiss 96 h LC50 11.0 - 15.0 mg/L Lepomis macrochirus 96 h LC50 = 54 mg/L Oryzias latipes 96 h LC50 = 28.2 mg/L Poecilia reticulata 96 h LC50 50.87 - 70.34 mg/L Poecilia reticulata 96 h	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50	2.65
Butane	No information available.	No information available.	No information available	No information available.	2.89
Ethyl benzene	EC50 = 11 mg/L Pseudokirchneriella subcapitata 72 h EC50 = 4.6 mg/L Pseudokirchneriella subcapitata 72 h EC50 > 438 mg/L Pseudokirchneriella subcapitata 96 h EC50 2.6 - 11.3 mg/L Pseudokirchneriella subcapitata 72 h EC50 1.7 - 7.6 mg/L Pseudokirchneriella subcapitata 96 h	LC50 11.0 - 18.0 mg/L Oncorhynchus mykiss 96 h LC50 = 4.2 mg/L Oncorhynchus mykiss 96 h LC50 7.55 - 11 mg/L Pimephales promelas 96 h LC50 = 32 mg/L Lepomis macrochirus 96 h LC50 9.1 - 15.6 mg/L Pimephales promelas 96 h LC50 = 9.6 mg/L Poecilia reticulata 96 h	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50	3.118
Methyl ethyl ketoxime	EC50 = 83 mg/L Desmodesmus subspicatus 72 h	LC50 777 - 914 mg/L Pimephales promelas 96 h LC50 = 760 mg/L Poecilia reticulata 96 h	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	750: 48 h Daphnia magna mg/L EC50	0.65

Persistence and Degradability
Bioaccumulation

No information available.

No information available.

Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
Container Disposal Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY ,ORM-D

TDG
Proper shipping name AEROSOLS
Hazard Class 2.1
UN-No UN1950
Description UN1950,AEROSOLS,2.1,LTD QTY

ICAO
Shipping Description DO NOT SHIP AIR

IATA
Shipping Description DO NOT SHIP AIR

IMDG/IMO
Proper Shipping Name AEROSOLS
Hazard Class 2
UN-No UN1950
EmS No. F-D, S-U
Description UN1950, AEROSOLS, 2.1, LTD QTY

15. REGULATORY INFORMATION

Inventories
TSCA Complies
DSL Complies
U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	Not applicable
Xylenes (o-, m-, p- isomers)	100 lb	Not applicable
Toluene	1000 lb	Not applicable
Ethyl benzene	1000 lb	Not applicable

16. OTHER INFORMATION

Prepared By Samantha Purvis
Supersedes Date 06/27/2013
Issuing Date 09/23/2016
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use,

processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.